



Material Specifications

Strip Curtains • Panel Curtains



1. Mount the rear track.



2. Hook curtains into place on the rear track.



3. Screw-in the face plate. Overlaps are automatically and perfectly aligned.



(Optional) Assemble the mounting first and then slide the curtains in.

Anti Static & Standard Vinyl Material Specifications

Standard Properties	Specification	Test Method
Hardness Durometer	79A	ASTM D-2240
Tensile Strength %	2400	ASTM D-412
Ultimate Elongation %	350	ASTM D-412
Ultimate Tear PSI	440	ASTM D-1004
100% Module PSI	1400	ASTM D-412
Brittle Temperature	-36°F / -38°C	
Min. Operating Temperature	0°F / -17° C	
Specific Gravity	1.21	
UV Stability	Excellent	
Flame Test (UL)	Pass	UV 94 V-O
Flame Test (NFPA)	Pass	NFPA 701 Small Scale
Anti Static Properties	Specification	Test Method
Surface Resistivity	$< 10^{12}$	ASTM D-257



Material Specifications


Strip Curtains • Panel Curtains



1. Mount the rear track.



2. Hook curtains into place on the rear track.



3. Screw-in the face plate. Overlaps are automatically and perfectly aligned.



(Optional) Assemble the mounting first and then slide the curtains in.

Polysim™ Material Specifications

Standard Properties	Specification	Test Method
Hardness Durometer	90A/47D	ASTM D-2240
Tensile Strength %	3800	ASTM D-412
Ultimate Elongation %	450	ASTM D-412
Ultimate Tear PSI		ASTM D-1004
100% Module PSI	1200	ASTM D-412
Brittle Temperature	0°F / -17°C	
Min. Operating Temperature	32°F / 0° C	
Specific Gravity	1.16	
UV Stability	Good	
Flame Test (UL)	Pass	UV 94 V-O
Flame Test (NFPA)	Pass	NFPA 701 Small Scale
Flame Test (ASTM)	10	ASTM E-84 Class 1
Smoke Test (ASTM)	180	ASTM E-84 Class 1
Anti Static Properties	Specification	Test Method
Surface Resistivity	< 10 ¹²	ASTM D-257