

ELIMSTAT GUN Part # 4011699

Balanced to 0 +/- 15V, the ElimStat Gun features high blow-off force to provide efficient cleaning and rapid static charge decay. A 0.01micron filter at the exit of the gun ensures the air is clean. The gun body is lightweight but durable. It features a light-touch trigger, making it comfortable even for extended use. All functionality is built into the gun: a flow control valve, a balance adjustment for calibration, and a two level LED which indicates both power and ionization. The gun and cable are static dissipative. A hanger is provided for easy mounting.

Features include:

- Filter at gun exit to ensure clean air
- Lightweight ergonomic design for user comfort
- Adjustable airflow control
- · Remote activation of ionization and air flow
- Ionization verification indicator light



SPECIFICATIONS

Discharge Time	1.5 sec at 6" and 30 psi ($1000V$ to $100V$)
Size (Power Supply)	6.45"H x 5.20"W x 3.35"D
Weight	6.5 oz. (Integral gun and 7' hose assembly)
Material	Static dissipative polycarbonate ABS blend
Air Flow	2.4 SCFM at 30 psi (68 1/min at 2 bar) 4.6 SCFM at 60 psi (130 1/min at 4 bar) 7.4 SCFM at 100 psi (210 1/min at 7 bar)

CORPORATE OFFICES: 888 Dayton Street Suite 105, Yellow Springs, OH 45387 www.bennettnbennett.com CUSTOMER SERVICE NUMBERS: (888) 4 BENNETT Phone: (937) 324-1100 Fax: (937) 324-8753